

Options and Compatibility

		unit							
		minCord	mC15	mC30	mC30Duo	mC50	mC50Duo	mC80	minCam360
cable	cable	Push-Pull	5mm Push-Pull or 5.6mm Push-Rod	6.7mm Push-Rod	6.7mm Push-Rod Push-Pull	9.2mm Push-Rod	9.2mm Push-Rod 6.7mm Push-Rod	11.2mm Push-Rod	9.2mm Push-Rod
	length (standart)	15m	30m	30m	30m 15m	60m	60m 20m	130m	60m
	max. length	30m	40m	50m	40m (6.7)	90m	90m 30m	130m	100m
camera	KK13	x	x		x				
	KK18	x	x	x	x	x	x	x	
	KK29(SL)			x	x	x	x	x	
	KK55(SL)					x	x	x	
	SK50								x
locating	keine	x	x	x	x	x	x	x	x
	512 Hz	x	x	x	x	x	x	x	
	640 Hz								x
	33k Hz	x	x	x	x	x	x	x	
monitor	8"		x	x	x	x	x	x	x
	5.6"		x	x	x	x	x	x	
	3.5"	x							
	none	x	x	x	x	x	x	x	x
options	textgenerator		optional	optional	optional	optional	optional	optional	optional
	metercounter		optional	optional	optional	optional	optional	optional	optional
	trolley					optional	optional	optional	optional

Options and Compatibility

	camera				
	KK13	KK18	KK29(SL)	KK55(SL)	SK50
∅ (mm)	15-100	20-200	30-300	60-400	70-400
without spacer	> 15	> 20	> 30	> 60	> 70
KK13 spacer D24	> 24				
KK18 spacer D29		> 29			
KK29(SL) spacer D45		> 45	> 45		
KK29(SL) brush D75		> 75	> 75		
KK29(SL) brush D105		> 105	> 105		
KK29(SL) brush D145			> 145		
roller skid - D115*			> 115		
exch. rolls 135			> 135		
exch. rolls 200			> 200		
KK55(SL) - D75				> 75	
roller skid >130				> 130	
exch. rolls >200				> 200	
roller skid >250 *				> 250	
roller skid >300 *with lamp				> 300	
RID					> 100
SK50 spacer D58					> 58
SK50 spacer D85					> 85
roller skid > 130					> 130
exch. rolls > 200					> 200
roller skid > 250 *					> 250
roller skid 300-500 *					> 300

* with additional pushrod